

MS2008B

600A AC MINI CLAMP METER



- 4000 counts LCD, max. display 3999
- Capacitance, frequency, duty cycle and temperature measurement
- Data hold for easy reading
- **Clamp light** and LCD backlit
- Auto/manual range, auto power off
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 600V

Technical specifications

DCV: 400m/4/40/400/600V, $\pm 0.8\%$

ACV: 4/40/400/600V, $\pm 1.0\%$

ACA: 4/40/400/600A, $\pm 3.0\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.2\%$

CAP: 50n/500n/5 μ /50 μ /100 μ F, $\pm 4.0\%$

FREQ: 50/500/5k/50k/100kHz, $\pm 1.0\%$

TEMP: $-20^{\circ}\text{C} \sim 750^{\circ}\text{C}$, $\pm 2.0\%$

Duty cycle: 1% \sim 99%, $\pm 3.0\%$

Audible continuity ($< 50 \Omega$) & diode test

Clamp size: $\Phi 26\text{mm}$ (max.)

Battery: 1.5Vx3, AAA size

Dimensions & weight: 280x78x35mm, 245g

Accessories: carrying bag, temp probe

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn