

MS2108A

400A AC/DC MINI CLAMP METER



- 4000 counts LCD display with bar-graph
- Min /Max and relative measurement
- Data hold for easy reading
- **Clamp light** and LCD backlit
- Auto ranging, auto power off
- Secondary injection molding case, safety as per IEC1010-1 CAT.III 600V

Technical specifications

DCV: 400m/4/40/400/1000V, $\pm 0.8\%$

ACV: 4/40/400/600V, $\pm 1.0\%$

DCA: 40/400A, $\pm 3.0\%$

ACA: 40/400A, $\pm 3.0\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 0.8\%$

CAP: 40n/400n/4 μ /40 μ /400 μ /4mF, $\pm 4.0\%$

FREQ: 10 ~10MHz, $\pm 0.5\%$ (from test leads)

FREQ: 40 ~10kHz, $\pm 1.5\%$ (from current clamp)

Duty cycle: 10% ~95%, $\pm 3.0\%$

Audible continuity & diode test

Clamp size: $\Phi 26\text{mm}$ (max.)

Battery: 1.5Vx3, AAA size

Dimensions & weight: 280x78x35mm, 245g

Accessories: carrying bag

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn