



MS2203 True RMS DIGITAL POWER CLAMP METER

- 9999 counts multiple LCD display with bar graph and backlit
- Measures AC Voltage, Current, Frequency, VA, W, VAR, KWh, Power Factor of single or three phase (3/4-wire) electric network
- **Data logging:** storage for 28 measures
- Displays power parameters of each phase
- Displays kWh value and measuring time
- Auto-ranging, **True RMS** AC measurement
- **RS232 interface** and Win graphics software
- Data-hold, Max /Min value measurement
- Safety as per IEC1010-1 Cat III 600V

Technical specifications

ACV: 100/300/600V, $\pm 1.2\%$

ACA: 40/100/400/1000A, $\pm 2.0\%$

FREQ: 20Hz ~1kHz, $\pm 0.5\%$

KVA: 4k/10k/40k/100k/600kVA, $\pm 3.0\%$

KW: 4k/10k/40k/100k/600kW, $\pm 3.0\%$

KVar: 4k/10k/40k/100k/600kVar, $\pm 4.0\%$

KWh: 0.001kWh ~10,000kWh, $\pm 3.0\%$

PF ($\cos \phi$): 0.3 cap ~ 0.3 ind, ± 0.02

Clamp sized: $\Phi 50\text{mm}$ max.

Dimensions & weight: 300x103x51mm, 640g

Accessories: plastic carrying case

Battery: 1.5Vx4, AA size

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn