

MS84

HIGH SAFETY DMM, ELEGANT DESIGN

- 3 1/2 digits LCD display with backlit
- 10A or 20A fused (20A version without CE approval), full overload protection
- Audible continuity and diode test
 Data hold, auto power-off
- Elegant design with integrated holster
- Safety as per IEC1010-1, Cat.III 1000V & Cat.IV 600V

Technical specifications

DCV: 200m/2/20/200/1000V, ±0.5% ACV: 2/20/200/750V, ±0.8%

DCA: 20m/200m/10A. ±1.5%

ACA: 20m/200m/10A, ±1.5% ACA: 20m/200m/10A, ±1.8%

OHM: $200/2k/20k/200k/2M/20M/200M\Omega$, $\pm 0.8\%$ CAP: $20n/200n/2\mu/200\mu$ F, $\pm 4.0\%$

FREQ: 20kHz. ±1.5%

TEMP: -20° ~1000 °C, $\pm 2.0\%$ Audible continuity and diode test

Audible continuity and diode test Transistor h_{ee} test: 0~1000

Battery: 9Vx1, 6F22

Dimensions: 188x92x50mm, 380g approx.
Accessories: temperature probe

www.peak-meter.cr

PEAKMETER®

by Sinometer

Email: sales@peak-meter.cn