



PM2028A True RMS

1000A AC AUTO-RANGING CLAMP METER

- 6,000 counts LCD dual display
- Non-contact AC voltage detection (**NCV**)
- **True RMS** AC measurement
- Frequency measurement by clamp or leads
- Data hold, **torch light** and LCD backlit
- Relative value measurement
- Auto /manual ranging, auto power off
- Safety as per IEC1010-1 CAT.III 1000V

Technical specifications

DCV: 6/60/600/1000V, $\pm 1.0\%$

ACV: 6/60/600/1000V, $\pm 1.2\%$

ACA: 6/60/600/1000A, $\pm 3.0\%$

OHM: 600/6k/60k/600k/6M/60M Ω , $\pm 1.0\%$

CAP: 100n/1 μ /10 μ /100 μ /1m/10mF, $\pm 3.0\%$

FREQ: 10Hz~10kHz, $\pm 0.5\%$

TEMP: -20 $^{\circ}$ C~1000 $^{\circ}$ C, -4 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 2.0\%$

Audible continuity: <30 Ω

Clamp size: $\Phi 35$ mm (max.)

Battery: 1.5Vx3, AAA size

Dimensions: 235x85x40mm, 380g approx.

Accessories: carrying bag, temp probe

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn