



PM2118

600A AC/DC CLAMP METER, AUTO-RANGING

- 6,000 counts LCD dual display with backlit
- Non-contact AC voltage detection (**NCV**)
- **LPF** (low-pass filter) of 1kHz, 3dB.
- **LowZ** function for ACV detect /measurement
- Frequency measurement by clamp or leads
- Data hold, auto power off
- Safety as per IEC1010-1 CAT.III 600V

Technical specifications

DCV: 600m/6/60/600V, $\pm 0.5\%$

ACV /LowZ (40~65Hz): 6/60/600V, $\pm 0.8\%$

DC μ A: 200 μ A, $\pm 0.8\%$; DCA: 60/600A, $\pm 3.0\%$

ACA(40~65Hz): 60/600A, $\pm 2.5\%$

OHM: 600/6k/60k/600k/6M/10M Ω , $\pm 0.8\%$

CAP: 600 μ /6000 μ F, $\pm 3.0\%$

FREQ: 40Hz~1kHz, $\pm 1.0\%$

TEMP: -40 $^{\circ}$ C~1000 $^{\circ}$ C, -40 $^{\circ}$ F~1832 $^{\circ}$ F, $\pm 1.0\%$

Audible continuity: <30 Ω

Clamp size: $\Phi 24$ mm (max.)

Battery: 1.5Vx2, AAA size

Dimensions: 187x65x38mm, 250g approx.

Accessories: carrying bag, temp probe

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn