



PM2128S

SMART 1000A AC/DC CLAMP METER

- New generation **intelligent** (auto function & auto range) meter, just turn on and measure!
- 6,000 counts LCD dual display with bar-graph
- Non-contact AC voltage detection (**NCV**)
- **VFD** (variable-frequency drive) AC measurement
- Frequency measurement by clamp or leads
- Data hold, Peak Max value measurement
- Auto power off, torch light & LCD backlit
- Safety as per IEC1010-1 CAT.IV 600V

Technical specifications

DCV: 6/60/600V, min 0.5V; $\pm 0.5\%$

ACV(40~65Hz): 6/60/600V, min 1.0V; $\pm 0.8\%$

DCA: 60/600/100A, min 500mA; $\pm 3.0\%$

ACA(40~65Hz): 60/600/1000A, min 10mA; $\pm 2.5\%$

PEAK ACA: 10A~1500A, $\pm 10\%$

OHM: 6k/60k/600k/6M/10M Ω , $\pm 0.8\%$

CAP: 0.1 μ F~6000 μ F, $\pm 4.0\%$

FREQ: 40Hz~1kHz, $\pm 1.0\%$

Audible continuity: <30 Ω

Clamp size: $\Phi 35$ mm (max.)

Battery: 1.5Vx3, AAA size

Dimensions: 235x85x40mm, 380g approx.

Accessories: carrying bag

PEAKMETER[®]

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn