



PM6501A

DIGITAL THERMOMETER

- 9999 counts LCD display
- Supports 7 types of thermocouple
- Data hold for easy reading
- Displays in $^{\circ}\text{C}$ or $^{\circ}\text{F}$ switchable
- Elegant design, easily fits in shirt pocket

Technical specifications

Thermocouple: K, J, T, E, R, S, N

Temperature:

K: $-200^{\circ}\text{C} \sim 1372^{\circ}\text{C}$ / $-328^{\circ}\text{F} \sim 2501^{\circ}\text{F}$;

J: $-210^{\circ}\text{C} \sim 1200^{\circ}\text{C}$ / $-346^{\circ}\text{F} \sim 2192^{\circ}\text{F}$;

T: $-250^{\circ}\text{C} \sim 400^{\circ}\text{C}$ / $-418^{\circ}\text{F} \sim 752^{\circ}\text{F}$;

E: $-150^{\circ}\text{C} \sim 1000^{\circ}\text{C}$ / $-238^{\circ}\text{F} \sim 1832^{\circ}\text{F}$;

R: $0^{\circ}\text{C} \sim 1767^{\circ}\text{C}$ / $32^{\circ}\text{F} \sim 3212^{\circ}\text{F}$;

S: $0^{\circ}\text{C} \sim 1767^{\circ}\text{C}$ / $32^{\circ}\text{F} \sim 3212^{\circ}\text{F}$;

N: $-200^{\circ}\text{C} \sim 1300^{\circ}\text{C}$ / $-328^{\circ}\text{F} \sim 2372^{\circ}\text{F}$

Resolution: 0.1°C / 1°C / 1°F

Best accuracy: $\pm 1.0\% \pm 2^{\circ}\text{C}$

Dimensions: 130x63x27mm, 150g approx.

Power: 1.5Vx2, AA size

Accessories: K-type temp probe

PEAKMETER®

by Sinometer

www.peak-meter.cn

Email: sales@peak-meter.cn